

123 587

NC-Anbohrer HSS-E05+X.Cut 120° Lang HSS-E05 NC Spotting Drills+X.Cut 120° Long Series



- Formgenauer Präzisionsanschliff
- Lange Version für Zugangsprobleme
- Hohe Rundlauf- und Formgenauigkeit
- Glatter Zylinderschaft mit Toleranz h6
- Senkwinkel 120°
- Oberfläche X.5 Cut beschichtet

- High precision point geometry
- Long version for access problems
- High concentricity
- Straight shank in tolerance h6
- Point angle 120°
- With X5.Cut coating



| | |
|-----------|--------|
| HSS E05 | X Cut |
| ISO 10898 | 120° |
| DIN 1835A | L lang |

B

| ØD h6 | Ød2 h6 | L | l1 | Art. No. | Stk/pce Euro | ØD h6 | Ød2 h6 | L | l1 | Art. No. | Stk/pce Euro |
|----------|-----------|-----|----|------------|-----------------|----------|-----------|-----|----|------------|-----------------|
| 1 | 1 | 50 | 6 | 1235870100 | 46,20 | 8 | 8 | 140 | 25 | 1235870800 | 44,60 |
| 2 | 2 | 60 | 8 | 1235870200 | 42,80 | 10 | 10 | 170 | 25 | 1235871000 | 47,50 |
| 3 | 3 | 80 | 10 | 1235870300 | 40,00 | 12 | 12 | 170 | 30 | 1235871200 | 59,00 |
| 4 | 4 | 100 | 12 | 1235870400 | 35,40 | 16 | 16 | 200 | 35 | 1235871600 | 92,20 |
| 5 | 5 | 120 | 15 | 1235870500 | 35,70 | 20 | 20 | 200 | 40 | 1235872000 | 116,70 |
| 6 | 6 | 140 | 20 | 1235870600 | 36,90 | | | | | | |