

124 627

NC-Anbohrer HSS-E05+X.Cut DuoMag Doppelseitig 60° L:150
HSS-E05 NC Spotting Drills+X.Cut DuoMag Double 60° L:150



- Anbohren und Zentrieren
- Sonderanschliff mit verstärkter Spitze
- Spitzenwinkel 118°, Senkwinkel 60°
- Doppelseitig: 1 DuoMag = 2 Anbohrer
- Oberfläche X5.Cut beschichtet
- Spotting and centering
- Special geometry, reinforced point
- Point 118°, chamfering angle 60°
- Double: 1 DuoMag = 2 spotting drills
- With X5.Cut coating



HSS E05	X Cut
60°	2 ENDS
OAL 150	

B




124627 - OAL:150


ØD h7	Ød2 ±0,2	L ±1	a ±1°	Art. No.	Stk/pce Euro	ØD h7	Ød2 ±0,2	L ±1	a ±1°	Art. No.	Stk/pce Euro
8	2,5	150	60°	1246270800	37,50	16	4	150	60°	1246271600	64,80
10	3	150	60°	1246271000	43,20	20	5	150	60°	1246272000	92,20
12	3,5	150	60°	1246271200	46,10						

— INFO —


— INFO —



Zentrieren
Centering



Senken
Chamfering



Umfangsfasen
Longitudinal
Chamfering

