

155 200

Flachsenker HSS-E05 180°
HSS-E05 Piloted Counter Bores 180°



- Flachsenker mit Führungszapfen
- Innensechskant-, Zylinderschraube
- Für Durchgangsbohrungen (F,M)
- Gewindekernlöcher (K)
- Senkwinkel 180°
- Oberfläche blank

- Counter bores with fixed pilot
- For cheese, fillister screw caps
- For through holes (Fine, Medium)
- Tapping holes (K)
- Chamfering angle 180°
- Bright finish



HSS E05	blank
DIN 373	180°
z:3	ZYL

ØM	ØD	Ød	Ød2	L	z	Typ	Art. No.	Stk/pce	ØM	ØD	Ød	Ød2	L	z	Typ	Art. No.	Stk/pce
	z9	e8	z9					Euro		z9	e8	z9					Euro
1	2,2	1,1	2,2	45	3	F	155200010F	13,20	4	8	4,3	8	71	3	F	155200040F	11,00
1,2	2,5	1,3	2,5	45	3	F	155200012F	12,70	4	8	3,3	8	71	3	K	155200040K	11,00
1,4	2,8	1,5	2,8	45	3	F	155200014F	12,70	4	8	4,5	8	71	3	M	155200040M	11,00
1,6	3,3	1,7	3,3	56	3	F	155200016F	12,70	5	10	5,3	10	80	3	F	155200050F	11,90
1,7	3,8	1,8	3,8	56	3	F	155200017F	12,70	5	10	4,2	10	80	3	K	155200050K	12,10
2	4,3	2,2	4,3	56	3	F	155200020F	8,80	5	10	5,5	10	80	3	M	155200050M	11,90
2	4,3	2,4	4,3	56	3	M	155200020M	8,80	6	11	6,4	11	80	3	F	155200060F	12,80
2,2	4,6	2,4	4,6	56	3	F	155200022F	19,30	6	11	5	11	80	3	K	155200060K	14,30
2,5	5	2,7	5	56	3	F	155200025F	9,35	6	11	6,6	11	80	3	M	155200060M	12,80
2,5	5	2,9	5	56	3	M	155200025M	9,35	8	15	8,4	12,5	100	3	F	155200080F	20,50
2,6	5,5	2,8	5,5	71	3	F	155200026F	9,95	8	15	6,8	12,5	100	3	K	155200080K	21,00
2,6	5,5	3	5,5	71	3	M	155200026M	9,95	8	15	9	12,5	100	3	M	155200080M	20,50
3	6	3,2	6	71	3	F	155200030F	10,45	10	18	10,5	12,5	100	3	F	155200100F	24,60
3	6	2,5	6	71	3	K	155200030K	10,45	10	18	8,5	12,5	100	3	K	155200100K	43,10
3	6	3,4	6	71	3	M	155200030M	10,45	10	18	11	12,5	100	3	M	155200100M	24,60
3,5	6,5	3,7	6,5	71	3	F	155200035F	11,00	12	20	13	12,5	100	3	F	155200120F	27,60
3,5	6,5	2,9	6,5	71	3	K	155200035K	11,00	12	20	10,2	12,5	100	3	K	155200120K	27,60
3,5	6,5	3,9	6,5	71	3	M	155200035M	11,00	12	20	14	12,5	100	3	M	155200120M	27,60

— INFO —

— INFO —



Zapfensenker aus HSS-E in Sätzen

- 6 Stück im Satz - M3, M4, M5, M6, M8, M10
- Senkwinkel 90° - 180°
- Blank oder mit A.Cut Beschichtung
- Verschiedene Zusammenstellungen

HSS-E Piloted Counter Sinks in Sets

- Set of 6 pieces - M3, M4, M5, M6, M8, M10
- Chamfering angles 90° - 180°
- Uncoated or with A.Cut coating
- Different compositions



F