

342 600**Gewindebohrer HSS-E M - Form C Toleranz 6G**
HSS-E Taps M - Form C Tolerance 6G

- Allgemeine Anwendung
- Gedrallt für Grundlöcher bis $2 \times \emptyset$
- Kurzer Anschnitt 2-3 Gang
- Toleranz 6G
- Bis M10 mit verstärktem Schaft
- Oberfläche blank

- General use
- Spiral flutes for blind holes $2 \times \emptyset$
- Short chamfer 2-3 threads
- Tolerance 6G
- Up to M10 with reinforced shank
- Bright finish



HSS E05	blank
DIN 371	Form C35
DIN 376	Iso2 6G
ZYL	M

M	Stg TPI	L	l1	Ød2	Øa	Art. No.	Stk/pce Euro
3	0,5	56	7	3,5	2,7	3426000300	17,49
4	0,7	63	8,5	4,5	3,4	3426000400	17,79
5	0,8	70	10	6	4,9	3426000500	18,09
6	1	80	12	6	4,9	3426000600	18,49

M	Stg TPI	L	l1	Ød2	Øa	Art. No.	Stk/pce Euro
8	1,25	90	15	8	6,2	3426000800	21,29
10	1,5	100	17,5	10	8	3426001000	25,59
12	1,75	110	18	9	7	3426001200	31,69

M