

123 400

Kurzstufenbohrer HSS-E05 90°  
HSS-E05 Step Drills 90°



- Schraubendurchgangslöcher DIN 273
- Senkungen nach DIN 74
- Fluchtgenaues Bohren und Senken
- Ausführung fein, Senkwinkel 90°
- Oberfläche blank
- For through holes (DIN 273)
- For screws with chamfer 90°
- Drilling, chamfering in one operation
- High concentricity
- Bright finish



HSS E05 blank

90° ZYL



ØM	ØD	Ød	Ød2	L	l1	a	Art. No.	Stk/pce
	h9	±0,05	h9	±1	1	±1°		Euro
2	4,6	2,2	4,6	45	6	90°	1234000200	10,60
2,5	5,7	2,7	5,7	45	7	90°	1234000250	10,60
3	6,5	3,2	6,5	45	9	90°	1234000300	10,60
3,5	7,6	3,7	7,6	50	10	90°	1234000350	17,00
4	8,6	4,3	8,6	50	11	90°	1234000400	12,40

ØM	ØD	Ød	Ød2	L	l1	a	Art. No.	Stk/pce
	h9	±0,05	h9	±1	1	±1°		Euro
5	10,4	5,3	10,4	55	13	90°	1234000500	13,80
6	12,4	6,4	12,4	63	15	90°	1234000600	17,10
8	16,4	8,4	12,5	100	19	90°	1234000800	32,90
10	20,4	10,5	12,5	110	23	90°	1234001000	48,20
12	25	13	12,5	120	28	90°	1234001200	148,50

