

123 410**Kurzstufenbohrer HSS-E05 180°
HSS-E05 Step Drills 180°**

- Schraubendurchgangslöcher DIN 273
- Senkungen nach DIN 74
- Fluchtgenaues Bohren und Senken
- Ausführung fein, Senkwinkel 180°
- Oberfläche blank
- For through holes DIN 273
- For screws with chamfer 180°
- Drilling, chamfering in one operation
- High concentricity
- Bright finish



HSS E05 blank

180° ZYL



ØM	ØD	Ød	Ød2	L	l1	a	Art. No.	Stk/pce	ØM	ØD	Ød	Ød2	L	l1	a	Art. No.	Stk/pce
h9	h9	±0,05	h9	±1	1	±1°		Euro	h9	h9	±0,05	h9	±1	1	±1°		Euro
2	4,3	2,4	4,3	45	6	180°	1234100200	10,80	6	11	6,6	11	63	15	180°	1234100600	16,70
2,5	5	2,9	5	45	7	180°	1234100250	10,80	8	15	9	12,5	100	19	180°	1234100800	32,40
3	6	3,4	6	45	9	180°	1234100300	10,45	10	18	11	12,5	110	23	180°	1234101000	47,50
4	8	4,5	8	50	11	180°	1234100400	12,20	12	20	14	12,5	110	28	180°	1234101200	62,20
5	10	5,5	10	55	13	180°	1234100500	13,50	14	24	16	12,5	120	34	180°	1234101400	146,30

C